

AT - 1

Control panels for three-phase electric pumps - direct on line start

Tipo Type	P ₂ max		V 50Hz	I range A	Dimensioni Dimensions				Peso Weight kg
	kW	HP			H mm	L mm	W mm	Material	
AT1/ 0,5	0,37	0,5	3~ 400V	1,3 - 2,3	320	240	190	ABS	4
AT1/ 0,75	0,55	0,75	3~ 400V	1,3 - 2,3	320	240	190	ABS	4
AT1/ 1	0,75	1	3~ 400V	2,3 - 3,1	320	240	190	ABS	4
AT1/ 1,5	1,1	1,5	3~ 400V	3,1 - 4,2	320	240	190	ABS	4
AT1/ 2	1,5	2	3~ 400V	4,2 - 7,6	320	240	190	ABS	4
AT1/ 3	2,2	3	3~ 400V	4,2 - 7,6	320	240	190	ABS	4
AT1/ 4	3	4	3~ 400V	7,6 - 10	320	240	190	ABS	4,5
AT1/ 5,5	4	5,5	3~ 400V	10 - 13	320	240	190	ABS	4,5
AT1/ 7,5	5,5	7,5	3~ 400V	20 - 24	320	240	190	ABS	5,5
AT1/ 10	7,5	10	3~ 400V	20 - 24	320	240	190	ABS	5,5
AT1/ 12,5	9,2	12,5	3~ 400V	20 - 24	320	240	190	ABS	5,5
AT1/ 15	11	15	3~ 400V	24 - 29	320	240	190	ABS	5,5
AT1/ 17,5	12,5	17,5	3~ 400V	29 - 35	400	300	240	Metallic	12
AT1/ 20	15	20	3~ 400V	35 - 38	400	300	240	Metallic	12
AT1/ 25	18,5	25	3~ 400V	44 - 53	500	400	240	Metallic	15
AT1/ 30	22	30	3~ 400V	44 - 53	500	400	240	Metallic	15
AT1/ 40	30	40	3~ 400V	65 - 78	500	400	240	Metallic	15
AT1/ 50	37	50	3~ 400V	84 - 96	500	400	240	Metallic	18

