

AT - 2

Control panels for three-phase electric pumps - star/delta (Y/Δ) starting

Tipo Type	P ₂ max		V 50Hz	I range (57%) A	I max A	Dimensioni Dimensions				Peso Weight kg
	kW	HP				H mm	L mm	W mm	Material	
AT2/ 7,5	5,5	7,5	3~ 400/690V	7,6 - 10	19	390	310	175	ABS	6
AT2/ 10	7,5	10	3~ 400/690V	10 - 13	22	390	310	175	ABS	6
AT2/ 12,5	9,2	12,5	3~ 400/690V	10 - 13	22	390	310	175	ABS	6
AT2/ 15	11	15	3~ 400/690V	13 -16	30	390	310	175	ABS	6
AT2/ 20	15	20	3~ 400/690V	20 - 24	38	500	400	240	Metallic	16
AT2/ 25	18,5	25	3~ 400/690V	24 -29	48	500	400	240	Metallic	16
AT2/ 30	22	30	3~ 400/690V	29 - 35	52	500	400	240	Metallic	16
AT2/ 35	26	35	3~ 400/690V	29 - 35	62	500	400	240	Metallic	16
AT2/ 40	30	40	3~ 400/690V	35 - 38	72	500	400	240	Metallic	20
AT2/ 50	37	50	3~ 400/690V	44 - 53	86	600	400	240	Metallic	30
AT2/ 60	45	60	3~ 400/690V	50-60	105	600	400	240	Metallic	30
AT2/ 70	52	70	3~ 400/690V	57-67	120	700	500	290	Metallic	35
AT2/ 75	55	75	3~ 400/690V	57-67	120	700	500	290	Metallic	35
AT2/ 80	60	80	3~ 400/690V	65-78	130	700	500	290	Metallic	40
AT2/ 90	67	90	3~ 400/690V	75-87	142	700	500	290	Metallic	40
AT2/ 100	75	100	3~ 400/690V	84-96	160	800	600	380	Metallic	60
AT2/ 110	83	110	3~ 400/690V	80-110	190	800	600	380	Metallic	65
AT2/ 125	92	125	3~ 400/690V	80-110	190	800	600	380	Metallic	65
AT2/ 150-160	120	160	3~ 400/690V	100-135	240	1000	800	380	Metallic	65
AT2/ 180	132	180	3~ 400/690V	130-175	280	1000	800	380	Metallic	70
AT2/ 220	165	220	3~ 400/690V	150-200	320	1000	800	380	Metallic	80
AT2/ 300	220	300	3~ 400/690V	115-380	450	1200	800	380	Metallic	100

