

AT - 3

Control panels for three-phase electric pumps - impedance starting

Tipo Type	P ₂ max		V 50Hz	I range A	Dimensioni box Box dimensions				Peso Weight kg
	kW	HP			H mm	L mm	W mm	Material	
AT3/ 7,5	5,5	7,5	3~ 400V	16 - 20	500	400	240	Metallic	19
AT3/ 10	7,5	10	3~ 400V	20 - 24	500	400	240	Metallic	21
AT3/ 12,5	9,2	12,5	3~ 400V	20 - 24	500	400	240	Metallic	21
AT3/ 15	11	15	3~ 400V	24 - 29	500	400	240	Metallic	22
AT3/ 17,5	12,5	17,5	3~ 400V	29 - 35	500	400	240	Metallic	23
AT3/ 20	15	20	3~ 400V	35 - 38	600	400	240	Metallic	36
AT3/ 25	18,5	25	3~ 400V	36 - 47	700	500	290	Metallic	36
AT3/ 30	22	30	3~ 400V	44 - 53	700	500	290	Metallic	36
AT3/ 35	26	35	3~ 400V	50 - 60	700	500	290	Metallic	41
AT3/ 40	30	40	3~ 400V	57 - 67	800	600	380	Metallic	41
AT3/ 50	37	50	3~ 400V	75 - 87	800	600	380	Metallic	52
AT3/ 60	45	60	3~ 400V	80 -110	800	600	380	Metallic	78
AT3/ 65-70	52	70	3~ 400V	100 -135	900	600	380	Metallic	78
AT3/ 75	55	75	3~ 400V	100 -135	900	600	380	Metallic	78
AT3/ 75-80-85	63	85	3~ 400V	100 -135	900	600	380	Metallic	78
AT3/ 90-100	75	100	3~ 400V	130 -175	1000	800	380	Metallic	114
AT3/ 100	75	100	3~ 400V	150 - 200	1200	800	380	Metallic	120
AT3/ 127	92	127	3~ 400V	150 - 200	1200	800	380	Metallic	120
AT3/ 150	110	150	3~ 400V	115 - 380	1600	1000	480	Metallic	250
AT3/ 180	132	180	3~ 400V	115 - 380	1600	1000	480	Metallic	250
AT3/ 220	165	220	3~ 400V	115 - 380	1600	1000	480	Metallic	250
AT3/ 300	220	300	3~ 400V	150 - 500	1800	1000	480	Metallic	290

