

## AT - 5

### Control panels for three-phase electric pumps - soft starter

Tipo Type	P <sub>2</sub> max		V 50Hz	I max A	Dimensioni box Box imensions				Peso Weight kg
	kW	HP			H mm	L mm	W mm	Material	
AT5/ 7,5	5,5	7,5	3~ 400V	18	600	410	240	Metallic	18
AT5/ 10	7,5	10	3~ 400V	25	600	410	240	Metallic	22
AT5/ 12,5	9,2	12,5	3~ 400V	25	600	410	240	Metallic	22
AT5/ 15	11	15	3~ 400V	30	600	410	240	Metallic	25
AT5/ 17,5-20	15	20	3~ 400V	37	600	410	240	Metallic	27
AT5/ 25	18,5	25	3~ 400V	45	600	410	240	Metallic	30
AT5/ 30	22	30	3~ 400V	60	600	410	240	Metallic	35
AT5/ 35	26	35	3~ 400V	60	600	410	240	Metallic	35
AT5/ 40	30	40	3~ 400V	72	600	410	240	Metallic	45
AT5/ 40-50	37	50	3~ 400V	85	600	410	240	Metallic	45
AT5/ 55-60	45	60	3~ 400V	105	600	410	240	Metallic	47
AT5/ 75	55	75	3~ 400V	125	800	610	380	Metallic	58
AT5/ 80	60	80	3~ 400V	125	800	610	380	Metallic	58
AT5/ 100	75	100	3~ 400V	170	800	610	380	Metallic	72
AT5/ 125	92	125	3~ 400V	210	1000	810	380	Metallic	85
AT5/ 150	110	150	3~ 400V	250	1000	810	380	Metallic	270
AT5/ 180	132	180	3~ 400V	300	1000	810	380	Metallic	220
AT5/ 220	165	220	3~ 400V	370	1200	810	380	Metallic	350
AT5/ 300	220	300	3~ 400V	470	1200	810	380	Metallic	380

